

NBS & Gradus Specifications

Boulevard 1500 Secondary Barrier Carpet

Data Sheet: (sheet 1 of 1) June 2009

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Boulevard 1500 Secondary Barrier Carpet is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Matting, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: Boulevard 1500 Secondary Barrier Carpet
Colour (select as required): Calculus (LRV: 9.03), Marinus (LRV: 2.71), Tempestatas (LRV: 2.14), Terra (LRV: 10.89)
Fixing: adhesive – as per manufacturers instructions

Gradus Detailed Specification

Manufacturer: Gradus Matting, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: Boulevard 1500 Secondary Barrier Carpet
Product construction: Needlepunch
Surface yarn: 100% polypropylene
Dimensions / backing: 15m x 2m Rubber backing
Tufted pile weight: 1400g/m²
Total height: 9mm nominal
Total weight: 2150g/m²
Colour (select as required): Calculus (LRV: 9.03), Marinus (LRV: 2.71), Tempestatas (LRV: 2.14), Terra (LRV: 10.89)
Classification: Tested to BSEN 1307
Colour fastness tests:

Light BSEN ISO105-BO2:1999 Method 2	>6
Shampoo BS1006:UK-TB1990	5
Water BSEN ISO 105-E01:1996	5
Sea Water BSEN ISO105-E02:1996	5
Rubbing BSEN ISO105-X12:1995	4-5

Fire rating: Hot Metal Nut BS4790 Low Radius
Fixing: adhesive – as per manufacturers instructions

Description

Boulevard 1500 is a high performance, cost effective secondary barrier carpet that is easy to install and maintain. With excellent appearance retention properties, this hardwearing product is resistant to compression, offering excellent durability. Ideal for use in the education and leisure markets, Boulevard 1500 incorporates a ribbed design that provides an effective surface for the removal of dirt and moisture from foot and wheeled traffic.

Available in four carefully selected colours, Boulevard 1500 provides end users with a superior alternative to coir in line with the guidelines in BS8300:2009 and Approved Document M (2004), helping specifiers meet their duties under the Disability Discrimination Act (DDA).

Boulevard 1500 can be used in conjunction with Esplanade 1500 primary barrier matting to provide a fully co-ordinated barrier matting system.