

## NBS & Gradus Specifications

### Access Primary Barrier Matting

Data Sheet: (sheet 1 of 2) January 2012

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Access Primary Barrier Matting is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

#### NBS Specification

#### N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

#### 300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

**Manufacturer:** Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.  
Tel: 01625 428922 Fax: 01625 433939  
Website: [www.gradusworld.com](http://www.gradusworld.com) Email: sales@gradusworld.com

**Reference:** Access Primary Barrier Matting  
**Height (select as required):** 12mm or 17mm  
**Module colour (select as required):** Black, Grey  
**Wiper colour (select as required):** From Boulevard 6000 range: Atlantic (LRV: 1.90) Galaxy (LRV: 2.56), Indigo (LRV: 4.01), Nickel (LRV: 3.70), Nightfall (LRV: 1.48), Rosemary (LRV: 4.45), Shadow (LRV: 5.36), Walnut (LRV: 2.86)  
or From Boulevard 5000HD range: Corncrake (LRV: 9.52), Cuckoo (LRV: 5.63), Jackdaw (LRV: 1.73), Kestrel (LRV: 5.42), Moorhen (LRV: 2.98), Redpoll (LRV: 4.14), Shelduck (LRV: 5.20), Swallow (LRV: 2.08)  
**Fixing:** recessed in matwell or surface-mounted with ramping frame – as per manufacturers instructions

#### Gradus Detailed Specification

**Manufacturer:** Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.  
Tel: 01625 428922 Fax: 01625 433939  
Website: [www.gradusworld.com](http://www.gradusworld.com) Email: sales@gradusworld.com

**Reference:** Access Primary Barrier Matting  
**Module construction:** Synthetic rubber  
**Carpet wiper construction:** Patterned tufted cut pile  
**Yarn:** 100% Aquafil Altro Chroma Solution Dyed Nylon  
**Backing:** PVC non-woven primary backing  
**Total height (select as required):** 12mm or 17mm  
**Module colour (select as required):** Black, Grey  
**Wiper colour (select as required):** From Boulevard 6000 range: Atlantic (LRV: 1.90) Galaxy (LRV: 2.56), Indigo (LRV: 4.01), Nickel (LRV: 3.70), Nightfall\* (LRV: 1.48), Rosemary (LRV: 4.45), Shadow (LRV: 5.36), Walnut (LRV: 2.86)  
\* available in broadloom only or From Boulevard 5000HD range: Corncrake (LRV: 9.52), Cuckoo (LRV: 5.63), Jackdaw (LRV: 1.73), Kestrel (LRV: 5.42), Moorhen (LRV: 2.98), Redpoll (LRV: 4.14), Shelduck (LRV: 5.20), Swallow (LRV: 2.08)  
**Classification:** Tested to BSEN 1307  
**Fire rating:** Hot Metal Nut BS4790 (Low Radius)  
**Fixing:** recessed in matwell or surface-mounted with ramping frame – as per manufacturers instructions  
**Installation accessories available:**  
**UMFA12 / UMFA18 / UMFA25:** 12mm / 18mm / 25mm aluminium matwell frames  
**FRA031:** 25mm aluminium matwell frame  
**FRB026:** 25mm brass matwell frame  
**RAM012:** 12mm ramping strip  
**SPA012 / SPA017:** 12mm / 17mm PVC spacer strips

## NBS & Gradus Specifications

### Access Primary Barrier Matting

Data Sheet: (sheet 2 of 2) December 2008

#### Description

Access is a mid duty primary barrier mat suitable for areas of medium traffic. The mat is a moulded solid synthetic rubber unit available in either Grey or Black with a choice of 100% solution dyed nylon wipers, and is available in 17mm and 12mm thicknesses.

The 17mm mat is usually recessed into a matwell whereas the 12mm version can be surface mounted using the 12mm ramping profile. Modules are 2000mm wide x 500mm deep and are supplied oversize for trimming in on site. Access is supplied with appropriate compression strips to allow for small movements as a result of changes in ambient temperature. Access can be used in conjunction with Boulevard 6000 or Boulevard 5000HD secondary barrier carpet to provide a fully co-ordinated system.