




A wide choice of transition and threshold strip profiles with a variety of widths and top detailing such as knurling, rounded edges or simply flat and/or heavier bars for better fitting under doorways. This variety is to best customize residential finishing and adapt to any decorative environment. The extruded brass and aluminium models are suitable for heavier transit areas.

strip⁺tec™ ST/STB



STRIPTEC ST 38 A* Anodised Aluminium

A top knurled bar in silver color finish, gold or bronze. High tolerance to corrosion but limited resistance to mechanical impact. The mid-section thickness is 3,7 mm. Self-adhesive (A*A), Drilled (A*F) version.



	B=mm	Art.		Adhesive	Drilled
Material: Extruded anodised aluminium	38	ST	38	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	38	ST	38	AOA	AOF
	38	ST	38	ABA	ABF
Length: 2,70 metres					
: 0,90/1,35 metres					

STRIPTEC STB-OL* Polished Brass

The brass article ensures an excellent tolerance to impact and chemical environments. Therefore it is ideal for industrial or commercial areas where heavier transit occurs. Also suitable in residential areas where brass is always appreciated. The mid-section thickness is 1,5 mm. Self-adhesive (A*A), Drilled (A*F) version.



Material: Extruded Brass	30	STB	30	OLA	OLF
	35	STB	35	OLA	OLF
	40	STB	40	OLA	OLF
Finish: Polished (OL*)					
Length: 2,70 metres					
: 0,90/1,35 metres					

STRIPTEC ST 50 OL* Polished Brass

A heavy cambered brass profile with 5 mm, thickness mid-section. Designed to guarantee resistance to chemical and mechanical impact present in commercial or industrial areas with heavier transit. Self-adhesive (A*A), Drilled (A*F) version.



Material: Extruded Brass	50	ST	50	OLA	OLF
Finish: Polished (OL*)					
Length: 2,70 metres					

STRIPTEC STB 25 A* Anodised aluminium

This top grooved flat head profile has a silver, gold or bronze coating. Good anti-oxidation tolerance but less to mechanical impact. Mid-section thickness: 2,2 mm. Self-adhesive (A*A), Drilled (A*F) version.



Material: Extruded anodised aluminium	25	STB	25	ASA	ASF
	25	STB	25	AOA	AOF
	25	STB	25	ABA	ABF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)					
Length: 2,70 metres					
: 0,90/1,35 metres					

STRIPTEC STB 35 A* Anodised aluminium

This flat head aluminium smooth heavy duty aluminium profile is coloured finished in silver, gold or bronze. The pre-drilled version has its holes placed in the middle. One may opt for the side holes for the code L version. The mid-section thickness is 2,4 mm. Self-adhesive (A*A), Drilled (A*F) version.



Material: Extruded anodised aluminium	35	STB	35	ASA	ASF
	35	STB	35	AOA	AOF
	35	STB	35	ABA	ABF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)					
Length: 2,70 metres					
: 0,90/1,35 metres					

: Pre-cut length available in SELFLINE kit L= 0,90/1,35 m