

NBS & Gradus Specifications

Topguard Plain Primary Barrier Matting

Data Sheet: (sheet 1 of 1) March 2015

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Topguard Plain Primary Barrier Matting is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Matting, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: Topguard Plain Primary Barrier Matting

Construction (select as required): Closed or Open (5mm), Single or Double wipers, 12mm or 18mm height

Linking strip material (select as required): Aluminium

Wiper colour: Black

Fixing: recessed in matwell or surface-mounted with ramping frame – as per manufacturers instructions

Gradus Detailed Specification

Manufacturer: Gradus Matting, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: Topguard Plain Primary Barrier Matting

Construction (select as required): Closed or Open (5mm) construction, Single or Double wipers

Linking strip material (select as required): Aluminium

Wiper colour: Black

Total height (select as required): 12mm or 18mm

Classification: Tested to BSEN 1307

Fire rating: Hot Metal Nut BS4790 (Low Radius)

Fixing: recessed in matwell or surface-mounted with ramping frame – as per manufacturers instructions

Installation accessories available:

UMFA12 / UMFA18 / UMFA25: 12mm / 18mm / 25mm aluminium matwell frame

FRB026: 25mm brass matwell frame

RMF60: 12mm aluminium ramping frame

Description

Topguard Plain is a heavy duty primary barrier mat designed for external or internal use in the most demanding applications. Consisting of rubber wiper strips and linking strips in a choice of aluminium, Topguard Plain is available as either open (5mm) or closed construction, and in two thicknesses (12mm and 18mm) allowing a wide choice of product configurations to suit most applications. Topguard Plain is ideally suited to heavy foot and trolley traffic applications such as supermarkets, airports and department stores where both the cleaning of incoming foot and trolley traffic is essential. Topguard Plain has the additional benefit of being reversible where the mat is a true rectangle or square to give an extended product life. Topguard Plain can be manufactured to most shapes on approval of a template. Logos can also be incorporated subject to design acceptance.