GRADUS
contract interior solutions

NBS & Gradus Specifications

ARXT81

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for ARXT81 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, Sk11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: ARXT81 with Xtra-grip Plus Insert
Material: Mill finish aluminium with PVC inserts
Colour: Bone (LRV: 50.66), Cliff (LRV: 27.61), Conker (LRV: 7.85), Diamond (LRV: 81.58), Lunar (LRV: 39.74), Marl (LRV: 10.91), Navy (LRV: 5.94), Raven (LRV: 5.01), Sulphur (LRV: 51.11), Meltwater (LRV: 51.13), Vine (LRV: 53.04) (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions
or
Reference: ARXT81 with Xtra-grip Insert
Material: Mill finish aluminium with PVC inserts
Colour: Carbon (LRV: 5.01), Deepsea (LRV: 5.94), Iceberg (LRV: 81.58), Oat (LRV: 50.66), Pebble (LRV: 27.61), Rock (LRV: 10.91), Truffle (LRV: 7.85), Vapour (LRV: 39.74), Zest (LRV: 51.11), Breeze (LRV: 51.13), Pampas (LRV:53.04) (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions
or
Reference: ARXT81 with Interior Insert
Material: Mill finish aluminium with PVC inserts
Colour: Interior Insert: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Coffee (LRV: 6.05), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), Clay (LRV: 47.97), Jade (LRV: 53.98), Sky (LRV: 52.63), Wisp (58.17) (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

---

GRADUS
contract interior solutions

NBS & Gradus Specifications

ARXT81

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: ARXT81
Gauge: 2mm
Tread Dimension: 56mm
Riser Dimension: 40mm
Insert Width: 50mm
Channel: Single mill finished aluminium channel with slip-resistant PVC insert
Profile Shape: Bullnose
Insert Bond: Gradus Fusion advanced adhesive technology
Insert Type & Colour (select as required):
Xtra-grip Plus insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions), suitable for areas subject to regular cleaning such as catering and food preparation environments) in colour: Bone (LRV: 50.66), Cliff (LRV: 27.61), Conker (LRV: 7.85), Diamond (LRV: 81.58), Lunar (LRV: 39.74), Marl (LRV: 10.91), Navy (LRV: 5.94), Raven (LRV: 5.01), Sulphur (LRV: 51.11), Meltwater (LRV: 51.13), Vine (LRV: 53.04) **or**
Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions)) in colour: Carbon (LRV: 5.01), Deepsea (LRV: 5.94), Iceberg (LRV: 81.58), Oat (LRV: 50.66), Pebble (LRV: 27.61), Rock (LRV: 10.91), Truffle (LRV: 7.85), Vapour (LRV: 39.74), Zest (LRV: 51.11), Breeze (LRV: 51.13), Pampas (LRV:53.04) **or**
Interior Insert with low risk of slip in interior dry conditions (PTV 68) in colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Coffee (LRV: 6.05), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), Clay (LRV: 47.97), Jade (LRV: 53.98), Sky (LRV: 52.63), Wisp (58.17)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

---

Description

XT Range
A range of aluminium stair edgings incorporating an extended insert that continues around the leading edge of the profile to ensure that contact is always made with the slip resistant element of the stair edging in line with the latest research undertaken by BRE (Information Paper 15/03).
ARXT81 features tread and riser dimensions to meet the guidance in BS8300:2009+A1:2010 in order to help achieve an inclusive environment in line with the Equality Act 2010.