

NBS & Gradus Specifications

DDA4

Data Sheet: (sheet 1 of 2) October 2015

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for DDA4 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: DDA4 with Xtra-grip Plus Insert

Material: PVC-u channel with PVC insert

Channel Colour: Black (LRV: 4.99), Bluebell (LRV: 9.76), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Evergreen (LRV: 6.63), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54) (select as required)

Insert Colour: Bone (LRV: 50.66), Cliff (LRV: 27.61), Conker (LRV: 7.85), Diamond (LRV: 81.58), Lunar (LRV: 39.74), Marl (LRV: 10.91), Navy (LRV: 5.94), Raven (LRV: 5.01), Sulphur (LRV: 51.11), Meltwater (LRV: 51.13), Vine (LRV: 53.04) (select as required)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

or

Reference: DDA4 with Xtra-grip Insert

Material: PVC-u channel with PVC insert

Channel Colour: Black (LRV: 4.99), Bluebell (LRV: 9.76), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Evergreen (LRV: 6.63), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54) (select as required)

Insert Colour: Carbon (LRV: 5.01), Deepsea (LRV: 5.94), Iceberg (LRV: 81.58), Oat (LRV: 50.66), Pebble (LRV: 27.61), Rock (LRV: 10.91), Truffle (LRV: 7.85), Vapour (LRV: 39.74), Zest (LRV: 51.11), Breeze (LRV: 51.13), Pampas (LRV: 53.04) (select as required)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

or

Reference: DDA4 with Interior Insert/ Interior Insert - Grained

Material: PVC-u channel with PVC insert

Channel Colour: Black (LRV: 4.99), Bluebell (LRV: 9.76), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Evergreen (LRV: 6.63), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54) (select as required)

Insert Colour: Interior Insert: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Photoluminescent (LRV: 57.59; suitable for channels with a 50mm insert or less), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), Lead (LRV: 12.77) (select as required)

or Interior Insert – Grained: Black (LRV: 6.47), Brown (LRV: 12.13), Dove (LRV: 23.40), Granite (LRV: 13.44) (select as required)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

NBS & Gradus Specifications

DDA4

Data Sheet: (sheet 2 of 2) October 2015

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: DDA4

Gauge: 6mm

Tread Dimension: 55mm

Riser Dimension: 55mm

Insert Width: 50mm

Channel: Single PVC-u channel with slip-resistant PVC insert

Profile Shape: Rake Back

Channel Colour: Black (LRV: 4.99), Bluebell (LRV: 9.76), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Evergreen (LRV: 6.63), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54) (select as required)

Insert Bond: Gradus Fusion advanced adhesive technology

Insert Type & Colour (select as required):

Xtra-grip Plus insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions), suitable for areas subject to regular cleaning such as catering and food preparation environments) in colour: Bone (LRV: 50.66), Cliff (LRV: 27.61), Conker (LRV: 7.85), Diamond (LRV: 81.58), Lunar (LRV: 39.74), Marl (LRV: 10.91), Navy (LRV: 5.94), Raven (LRV: 5.01), Sulphur (LRV: 51.11), Meltwater (LRV: 51.13), Vine (LRV: 53.04) (select as required)

or

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions)) in colour: Carbon (LRV: 5.01), Deepsea (LRV: 5.94), Iceberg (LRV: 81.58), Oat (LRV: 50.66), Pebble (LRV: 27.61), Rock (LRV: 10.91), Truffle (LRV: 7.85), Vapour (LRV: 39.74), Zest (LRV: 51.11), Breeze (LRV: 51.13), Pampas (LRV: 53.04) (select as required)

or

Interior Insert / Interior Insert – Grained with low risk of slip in interior dry conditions (PTV 68). Interior Insert in colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Photoluminescent (LRV: 57.59; suitable for channels with a 50mm insert or less), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), Lead (LRV: 12.77) (select as required)

or Interior Insert – Grained: Black (LRV: 6.47), Brown (LRV: 12.13), Dove (LRV: 23.40), Granite (LRV: 13.44) (select as required)

Recommended Side Trims: HT44, HT42

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

DDA & RNC Range

A range of attractive and hardwearing stair edgings comprising of PVC-u channels with fusion bonded slip resistant inserts. DDA and RNC profiles incorporate an extended insert design to match the channel colour to provide additional slip resistance around the leading edge of the stair edging. This ensures that contact is always made with the slip resistant element of the stair edging. Suitable for interior use, these profiles are supplied with pre-bonded inserts and capping plugs to conceal screw heads after fixing. Typically used with resilient floorcoverings or carpet from all major manufacturers, Hardnose stair edgings are suitable for applications such as commercial office, retail and healthcare.

DDA4 incorporates a 55mm tread and 55mm riser to meet the guidance in Approved Document M (The Building Regulations 2010) and BS8300:2009+A1:2010 to help achieve an inclusive environment in line with the Equality Act 2010.