GRADUS
contract interior solutions

NBS & Gradus Specifications

ELA 31 40

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for ELA 31 40 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: ELA 31 40 with Interior Insert
Material: Mill finish aluminium with PVC inserts.
Colour: Interior Insert: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: ELA 31 40
Insert Reference: ELINS40
Insert Width: 40mm
Note: The PVC insert strips must be specified separately.
Gauge: 4mm
Tread Dimension: 53mm
Riser Dimension: 35mm
Channel: Single mill finished aluminium channel with slip-resistant PVC insert
Profile Shape: Kinked Face
Insert Bond: Gradus Fusion advanced adhesive technology
Insert Type & Colour (select as required):
Interior Insert with low risk of slip in interior dry conditions (PTV 68). Interior Insert in colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

Elite Range
A range of attractive and hardwearing stair edgings comprising of aluminium channels with fusion bonded slip resistant inserts. Suitable for interior use, the Gradus Elite range of stair edgings offers a concealed fixing as the inserts are bonded into the channel on site using a specialist double sided tape which is pre-bonded to the insert. A mechanical lock provided by the use of locating points also provides added reassurance. Typically used with heavy resilient floorcoverings and carpet from all major manufacturers, Elite aluminium stair edgings are suitable for all commercial and most industrial applications.

As with all Gradus stair edgings ELA 31 40 helps to meet the guidance in Approved Document M (The Building Regulations 2010) and helps to achieve an inclusive environment in line with the Equality Act 2010.