





roundcorner™ RO

ROUNDCORNER RO series comprises several corner protectors with rounded edge in order to best protect in compliance with the accident and injury prevention norms. In fact this profile is greatly used in commercial and industrial areas where intense transit occurs.


ROUNDCORNER can perfectly cover over chipped tiled corners and are supplied with self-adhesive glue strips with excellent hold which help absorb shock impact.



Stainless steel and Brass Section



Aluminium Section



ROUNDCORNER RO 25 A11A Self-Adhesive Powder Coated Aluminium

Profile varnished with a polyester powder coating. ROUNDCORNER is ready to be fixed onto the corners of the wall. It covers a width of 25 mm which thanks also to its rounded section satisfies both technical and safety requirements and domestic decor needs.

	AxB		Art.	
Material: Powder coated aluminium	25x25	RO	25	A11A
Finish: Pure white				
Length: 2,70 metres				

ROUNDCORNER RO 25 A*A Self-Adhesive Anodised Aluminium

The self-adhesive aluminium ROUNDCORNER rounded profile is ready to be fixed onto the corners of the wall. It covers a width of 25 mm. which satisfies both technical and safety requirements as well as for aesthetics in domestic areas.

Material: Extruded anodised aluminium	25x25	RO	25	ASA/AOA/ ABA
Finish: Silver (ASA), Gold (AOA), Bronze (ABA)				
Length: 2,70 metres				

ROUNDCORNER RO-ILA Stainless steel Polished self-adhesive

Corner protection stainless steel polished rounded profile is supplied in different sizes so it can meet several technical and safety requirements and norms present in hospitals, public and food processing plants.

Thickness RO 25: 1 mm

Thickness RO 30 / 40 / 50: 1,2 mm

Material: Stainless steel	25x25 30x30 40X40 50X50	RO RO RO RO	25 30 40 50	ILA ILA ILA ILA
Finish: Polished (ILA)				
Length: 2,70 metres				
Width: 25-50 mm				
Surface with protection film strip				

ROUNDCORNER RO-OLA Brass Polished self-adhesive

Corner protection brass profile with rounded corner and self-adhesive for a further decorative choice along with the suitability of safety regulations in public constructions and other required areas

Thickness RO 25: 1 mm

Thickness RO 30 / 40 / 50: 1,2 mm

Material: Laminated brass	25x25 30x30 40X40 50X50	RO RO RO RO	25 30 40 50	OLA OLA OLA OLA
Finish: Polished (OLA)				
Length: 2,70 metres				
Width: 25-50 mm				
Surface with protection film strip				