+


STAIRTEC SA is a full body aluminium product designed to ensure safety steps thanks to the carborundum anti-slip strip on its surface. This profile is ideal to apply on a pre-laid covering of industrial and/or commercial areas. It is suitable for restructuring jobs for compliance with safety norms. This profile can be either glued - the grooves on the lower side ensuring a perfect anchoring to the adhesive - or bolted with screws, which will be later covered by the carborundum strip.



stairtec™ SA



The product SWH is certified R13 (Anti-slip insert). Anti-slip properties. According to standard DIN 51130 (06/2004).





Anodised aluminium profile, silver, gold or bronze tone. It is suitable for both outdoor and/or indoor applications with good tolerance to oxidation. For high traffic installations we recommend to prefer the silver finish. Anti-slip strip 19 mm wide not applied to be ordered separately, available in black (C 51) or photoluminescent (CF).

	7

	BxH			
Material:	52x30	SA	52	ASN
Extruded anodised aluminium	52x30	SA	52	AON
Finish*: Silver (ASN), Gold (AON), Bronze (ABN)	52x30	SA	52	ABN
Length: 2,70 metres				

	mm x m	Art.		
Anti-slip strip black	19x18,3	SWH	19	C51
Anti-slip strip fotoluminescente	19x18,3	SWH	19	CF

STAIRTEC SA 65 ASN Extruded anodized aluminium- silver

Silver anodised aluminium profile. It is suitable for both outdoor and/or indoor applications with good tolerance to oxidation.

Black anti-slip strip 50 mm wide (C51)

	BxH	Art.		
Material: Extruded anodised aluminium	65x55	SA	65	ASN
Finish: Silver (ASN)				
Length: 2,70 metres				
	mm x m		Art.	