



STAIRTEC SR is a linear profile, which works very well as stair nosing for steps and finishing trim for all exposed corners, thanks to its quick and practical application covering perfectly well the tile gap over the step while protecting the edge. The SR trim has an extended vertical edge which serves to better cover and protect the joining surfaces or paint finishing, avoiding future fissuring.

Its particular section design makes it suitable to match two different floor thicknesses for example 10 and 12,5 mm with the same reversible profile. Vertical anchorage with dovetail internal cavity groove. Patented system.



Illustrated scale dimension 1:1 (SR 8/15*)



TRIMTEC SR-O* Brass

The particular straight edge cut profile guarantees protection of vulnerable edges of ceramic stairs. Brass suffers from continuous exposure to humidity leading to oxidation of the surface – a normal polish buffing will bring the product back to its original shine.



	H/H¹=mm	Art.		
Material: Brass	8/15 10/12,5	SR SR	8/15 10/12,5	ON/OL ON/OL
Finish:Natural (ON), Polished (OL)				
Length: 2,70 metres				
Improved anchoring on the vertical side				

TRIMTEC SR-AS Extruded anodized aluminium- silver

This profile has a silver coating and is suitable for both indoor or outdoor application with high tolerance to weather agents but less to mechanical impact. During installation excess adhesive and grout should be removed immediately to avoid stains. The exposed surface may change colour or darken in time. Where higher stresses are involved the use of brass profiles is recommended.

Material: Extruded anodised aluminium	8/15 10/12,5	SR SR	8/15 10/12,5	AS AS
Finish: Silver (AS)	·		,	
Length: 2,70 metres				
Improved anchoring on the vertical side				

TRIMTEC SR-I* Stainless Steel AISI 304 - DIN 1.4301

This stainless steel profile is AISI 304 standard which ensures high tolerance to corrosion found in laboratories or strong detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, hospitals, public toilets etc.

Available in polished (IL) or brushed (IS) version.

Material: Stainless Steel AISI 304	8/15 10/12,5	SR SR	8/15 10/12,5	IL/IS IL/IS
Finish: Polished (IL), Brushed (IS)				
Length: 2,70 metres				

CURVELINE

TRIMTEC SR seriess are also available with a special cut flange so they become formable for curved edges and inlays. To order: add the letter D to the product code – for further details see page 47.

