GRADUS
contract interior solutions

NBS & Gradus Specifications

RNRC511

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for RNRC511 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433949
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: RNRC511 with Xtra-grip Plus Insert
Material: PVC-u channel with PVC insert
Channel Colour: Black (LRV: 4.99), Buttercup (LRV: 62.62), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), (select as required)
Insert Colour: Bone (LRV: 50.66), Cliff (LRV: 27.61), Conker (LRV: 7.85), Diamond (LRV: 81.58), Lunar (LRV: 39.74), Marl (LRV: 10.91), Navy (LRV: 5.94), Raven (LRV: 5.01), Sulphur (LRV: 51.11), Meltwater (LRV: 51.13), Vine (LRV: 53.04) (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions
or
Reference: RNRC511 with Xtra-grip Insert
Material: PVC-u channel with PVC insert
Channel Colour: Black (LRV: 4.99), Buttercup (LRV: 62.62), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), (select as required)
Insert Colour: Carbon (LRV: 5.01), Deepsea (LRV: 5.94), Iceberg (LRV: 81.58), Oat (LRV: 50.66), Pebble (LRV: 27.61), Rock (LRV: 10.91), Truffle (LRV: 7.85), Vapour (LRV: 39.74), Zest (LRV: 51.11), Breeze (LRV: 51.13), Pampas (LRV:53.04) (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions
or
Reference: RNRC511 with Interior Insert/ Interior Insert - Grained
Material: PVC-u channel with PVC insert
Channel Colour: Black (LRV: 4.99), Buttercup (LRV: 62.62), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), (select as required)
Insert Colour: Interior Insert: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Linen (LRV: 38.59, Midnight (LRV: 6.56), Ocean (LRV: 8.00), Photoluminescent (LRV: 57.59; suitable for channels with a 50mm insert or less), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), (select as required) **or**
Interior Insert – Grained: Black (LRV: 6.47), Brown (LRV: 12.13), Dove (LRV: 23.40), Granite (LRV: 13.44) (select as required)
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

GRADUS
contract interior solutions

NBS & Gradus Specifications

RNRC511

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433949
Website: www.gradusworld.com Email: sales@gradusworld.com

Reference: RNRC511
Gauge: Ramped profile for use with resilient floorcoverings or where there is no floorcovering
Tread Dimension: 55mm (71mm including ramp)
Riser Dimension: 34mm
Insert Width: 50mm
Channel: Single PVC-u channel with slip-resistant PVC insert
Profile Shape: Square
Channel Colour: Black (LRV: 4.99), Buttercup (LRV: 62.62), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), (select as required)
Insert Bond: Gradus Fusion advanced adhesive technology
Insert Type & Colour (select as required):
Xtra-grip Plus insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions), suitable for areas subject to regular cleaning such as catering and food preparation environments) in colour: Bone (LRV: 50.66), Cliff (LRV: 27.61), Conker (LRV: 7.85), Diamond (LRV: 81.58), Lunar (LRV: 39.74), Marl (LRV: 10.91), Navy (LRV: 5.94), Raven (LRV: 5.01), Sulphur (LRV: 51.11), Meltwater (LRV: 51.13), Vine (LRV: 53.04) **or**
Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions)) in colour: Carbon (LRV: 5.01), Deepsea (LRV: 5.94), Iceberg (LRV: 81.58), Oat (LRV: 50.66), Pebble (LRV: 27.61), Rock (LRV: 10.91), Truffle (LRV: 7.85), Vapour (LRV: 39.74), Zest (LRV: 51.11), Breeze (LRV: 51.13), Pampas (LRV:53.04) **or**
Interior Insert / Interior Insert – Grained with low risk of slip in interior dry conditions (PTV 68). Interior Insert in colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Photoluminescent (LRV: 57.59; suitable for channels with a 50mm insert or less), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), (select as required) **or** Interior Insert – Grained in colour: Black (LRV: 6.47), Brown (LRV: 12.13), Dove (LRV: 23.40), Granite (LRV: 13.44)
Recommended Side Trims: HT38, HT42
Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

---

Description

DDA & RNC Range

A range of attractive and hardwearing stair edgings comprising of PVC-u channels with fusion bonded slip resistant inserts. DDA and RNC profiles incorporate an extended insert design to match the channel colour to provide additional slip resistance around the leading edge of the stair edging. This ensures that contact is always made with the slip resistant element of the stair edging. Suitable for interior use, these profiles are supplied with pre-bonded inserts and capping plugs to conceal screw heads after fixing. Typically used with resilient floorcoverings or carpet from all major manufacturers, Hardnose stair edgings are suitable for applications such as commercial office, retail and healthcare.

RNRC511 incorporates a 55mm tread (71mm including ramp) and 34mm riser to meet the guidance in Approved Document M (The Building Regulations 2010), and from expert bodies such as RNIB Access Consultancy Service, in order to help to achieve an inclusive environment in line with the Equality Act 2010.